

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

WHEEL  
PAINTS

- Product identifier
- Trade name:
- Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation Lacquer
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
WHEELPAINTS  
5 Millbrook Close  
Northampton  
NN5 5JF  
Fax.: +44(0)604757411  
e-mail:Info@wheelpaints.co.uk  
www.wheelpaints.co.uk
- Further information obtainable from:
- Emergency telephone number:

## 2 Hazards identification

- Classification of the substance or mixture
  - Classification according to Directive 67/548/EEC or Directive 1999/45/EC  
R10-52/53-66-67: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
  - Information concerning particular hazards for human and environment:  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotizing effect.
  - Classification system:  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- 
- Label elements
  - Labelling according to EU guidelines:  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
  - Risk phrases:  
10 Flammable.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.
  - Safety phrases:  
2 Keep out of the reach of children.  
13 Keep away from food, drink and animal feedstuffs.  
23 Do not breathe fumes/aerosol.  
25 Avoid contact with eyes.  
46 If swallowed, seek medical advice immediately and show this container or label. 51 Use only in well-ventilated areas.
  - Special labelling of certain preparations:  
Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat, Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacat. May produce an allergic reaction.

# Safety data sheet

g to 1907/2006/EC, Article 31

Version number 1

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

## 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	25-50%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ⚠ Xn R65 ⚠ Xi R37 ⚠ N R51/53 R10-66-67 ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335+H336	2.5-10%
CAS: 112-07-2 EINECS: 203-933-3	2-butoxyethyl acetate ⚠ Xn R20/21 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Xn R20/21; ⚠ Xi R38 R10 ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-10%
CAS: 41556-26-7 EINECS: 255-437-1	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacat ⚠ Xi R43 ⚠ N R50/53 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Sens. 1, H317	≤ 1.0%
CAS: 26761-45-5 EINECS: 247-979-2	neodecansäureglycidylester ⚠ Xi R38 ⚠ Xi R43 ⚠ N R51/53 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≤ 1.0%
CAS: 127519-17-9 ELINCS: 407-000-3	A mixture of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethyl-ethyl)-4-hydroxyphenyl]propionates ⚠ N R51/53 ⚠ Aquatic Chronic 2, H411	≤ 1.0%
CAS: 82919-37-7 EINECS: 280-060-4	Methyl-1,2,2,6,6-pentamethyl-4-piperidylsebacat ⚠ Xi R43 ⚠ N R50/53 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Sens. 1, H317	≤ 1.0%

- Additional information: For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

## 5 Firefighting measures

- Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: No special measures required.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures  
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:  
Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## 7 Handling and storage

- Handling:
  - Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
  - Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
  - Requirements to be met by storerooms and receptacles: No special requirements.
  - Information about storage in one common storage facility: Store away from foodstuffs.
  - Further information about storage conditions: Keep container tightly sealed.
  - Storage class: 3
  - Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

## - Control parameters

- <b>Ingredients with limit values that require monitoring at the workplace:</b> 123-86-4 n-butyl acetate	
<b>WEL</b>	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
112-07-2 2-butoxyethyl acetate	
<b>WEL</b>	Short-term value: 50 ppm Long-term value: 20 ppm Sk
1330-20-7 xylene	
<b>WEL</b>	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV

- Additional information: The lists valid during the making were used as basis.

## - Exposure controls

### - Personal protective equipment:

### - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

### - Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### - Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### - Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### - Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

### - Information on basic physical and chemical properties

### - General Information

### - Appearance:

Form:

Fluid

Colour:

According to product specification

- Odour:

Characteristic

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

(Contd. of page 4)

· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124°C
· Flash point:	36°C (DIN 53213)
· Ignition temperature:	280°C (DIN 51794)
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20°C:	10.7 hPa
· Density at 20°C:	0.995 g/cm <sup>3</sup> (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Segregation coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20°C:	90 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	50.4 %
VOC (EC)	501.5 g/l
Solids content (weight-%):	49.6 %
· Other information	No further relevant information available.

## 10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Carbon monoxide

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

## 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values relevant for classification: 64742-

95-6 Solvent naphtha (petroleum), light arom.

<i>Oral</i>	<i>LD50</i>	>6800 mg/kg (rat)
<i>Dermal</i>	<i>LD50</i>	>3400 mg/kg (rab)
<i>Inhalative</i>	<i>LC50/4 h</i>	>10.2 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

## 12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes:  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

## 14 Transport information

· Land transport ADR/RID (cross-border)



- ADR/RID class: 3 (F1) Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1263
- Packaging group: III
- Hazard label: 3
- UN proper shipping name: 1263 PAINT, special provision 640E
- Tunnel restriction code D/E
- Remarks: ≤ 450 l: -

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1263
- Label: 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: PAINT
- Remarks: ≤ 30 l: -

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1263
- Label: 3
- Packaging group: III
- Proper shipping name: PAINT

- Special precautions for user Warning: Flammable liquids.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

· Information about limitation of use:

112-07-2	2-butoxyethyl acetate	4
100-41-4	Ethylbenzene	3A

Class	Share in %
NK	50-100

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 1

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### - Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin. R37 Irritating to respiratory system.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not to be considered as a guarantee of the products properties.