

Specialist Paints for the Alloy Wheel Industry

MATERIAL SAFETY DATA SHEETS

1. Identification of the substance and of the company/undertaking

Product Details:

Product Name: Sparkle 2 Silver

Application of the substance/ the preparation: Gloss Smooth Bonded Metallic

Supplier: WHEELPAINTS

NN5 5JF

UNITED KINGDOM

Tel: 01604 600582

E-mail: esales@wheelpaints.co.uk

www.wheelpaints.co.uk

2. Identified Uses

Coating powder

Based on use descriptor system given by guideline of the European Chemical

Revision Date: 23rd October 2018

Agency

Sector of use SU 3

Product category PC9a, PC9b

Further information see chapter Exposure scenario

The product is only for industrial and/or professional use, not for any private

consumer use.

3. Hazards Identification

This product is not classified as dangerous according to Regulation (EC) No.1272/2008.

Classification of the substance or mixture

According to Regulation (EC) No 1272/2008

Not applicable

Label elements

Labelling according to Regulation (EC) No 1272/2008.

None

Other hazards

May form explosible dust-air mixture if dispersed.

Restricted to professional users.

Mixtures

Chemical characterization

Mixture of synthetic resins and pigments

Hazardous components

Substances presenting a health or environmental hazard within the meaning of Regulation (EC) No 1272/2008

The product contains no substances classified as hazardous to health in concentrations which should be considered.

Other reporting relevant substances

CAS Not available Coating powder inhalable

no registration number

EC REACH available 95.00 <100.00%

Classification

CAS Not available Coating powder respirable

no registration number

EC REACH available 7.00 < 10.00 %

Classification

Up to the given revision date of this safety data sheet no REACH registration numbers are assigned to the chemical substances used in this preparation.

4. First Aid Measures

Description of first aid measures

General advice

When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

Inhalation

Avoid breathing dust. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

Skin contact

Do NOT use solvents or thinners. Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Ingestion

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label.

Most important symptoms and effects, both acute and delayed

Please see practical experience in section 11.

Indication of any immediate medical attention and special treatment needed

If unconscious place in recovery position and seek medical advice.

5. Fire Fighting Measures

Extinguishing media

Suitable extinguishing media

For metal containing products, do not use water or foam. Smother with a suitable dry chemical extinguisher agent or sand.

Extinguishing media which shall not be used for safety reasons

High volume water jet Water spray

Special hazards arising from the substance or mixture

Hazardous combustion products

Fire will produce dense black smoke containing hazardous combustion products. Exposure to decomposition products may be a hazard to health.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

Advice for firefighters

Fire and Explosion Hazards

Avoid water except to cool adjacent materials. The product itself does not burn.

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary.

Do not allow run-off from firefighting to enter drains or water courses.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Air out the room. Do not breathe dust.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems. Please avoid any emission of volatile organic compounds as possible.

Methods and materials for containment and cleaning up

Contain and collect spillage with an electrically protected vacuum cleaner or by wet brushing and place in container for disposal according to local regulations. Do not use a dry brush as dust clouds or static can be created! Use a suitable vacuum cleaner.

Reference to other sections

Comply with safety directives (see chapters 7 and 8).

7. Handling and Storage

It is recommended that advice is taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

Precautions for safe handling

Safe handling advice

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing. Keep away from open flames, hot surfaces and sources of ignition.

Smoking, eating and drinking should be prohibited in the application area.

Electrical equipment and lighting should be protected to appropriate standards to prevent dust meeting hot surfaces, sparks or other ignition sources. For personal protection see section 8. Comply with the health and safety at work laws. If material is a

coating, do not sand, flame cut, braze or weld dry coating without an appropriate respirator or appropriate ventilation, and gloves.

Advice on protection against fire and explosion

Always keep in containers of same material as the original one. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Observe label precautions. Refer to Technical Data Sheet (TDS) for further information about storage temperature. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

Specific end use(s)

Please see exposure scenarios as given in the annex.

8. Exposure controls and personal protection

Control parameters

DNEL

No information available.

PNEC

No information available.

Community / national occupational exposure limits

CAS-No.	Chemical name	Source Time	Туре	Value	Note
				10	-
	Coating powder inhalable			mg/m3	3
	Coating powder respirable			4 mg/m3	3
Glossary					

Indicative Occupational IOELVExposure Limits

TWA Time weighted average

Exposure controls

Additional technical information on the plant

Do not breathe dust. Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- using a local exhaust ventilation. If these are not enough to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

If dust formation exceeds the air concentration limits, then a respiratory protection device approved for this purpose must be worn.

Hand protection

The selected protective gloves must satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

	Glove Glove thickness B		ckness Break
Chemical name	material	through time	
	Nitrile	0.33	
	rubber	mm	> 240 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). After contamination, the glove must be changed. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately. Preventive skin protection such as skin protective cream is recommended. Work tasks should be arranged in such a way that gloves do not have to be worn continuously.

Eye protection

Eye protection (to EN 166/170) designed to protect against exposure to dusts should be worn when there is a likelihood of exposure.

Skin and body protection

Wear suitable protective clothing. Care should be taken in the selection of protective clothing. Avoid contact with the powder on throat and wrists due to possible inflammation and irritation of the skin.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

Environmental exposure controls

Do not let product enter drains.

For ecological information refer to section 12.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance

Form: solid Colour: grey Odour: Odour is not perceptible.

Important health, safety and environmental information

	Property	Value	Method
-	рН	Not applicable	_
	Melting point/freezing point	Not applicable.	
	Boiling point/boiling range	Not applicable.	
	Flash point	Not applicable.	EN ISO 3679
	Evaporation rate	Not applicable	
	Flammability (solid, gas)	No data available	
	Lower explosion limit	20 g=m ³	
	Upper explosion limit	Not applicable.	
	Vapour pressure	Not applicable.	
	Vapour density	No data available	
	Density	1.22 g=cm ³	20 C - DIN 53217/ISO 2811
	Solubility(ies)		
	Water solubility	moderate	

Solubility in other

solvents

No data available

This product is a mixture. For

Partition coefficient:

ingredient details see

n-octanol/water

section 12

Minimum ignition

energy

15 - 60 mJ

CEN TC 305

Decomposition

This product is a mixture. For further

temperature

information see

section 10.

Viscosity (23 C)

solid

Explosive properties

Not explosive

Oxidizing properties

not oxidizing

Other information

Content of volatile components

0.0

Basis Vapour pressure >= 0.01 kPa

(including water)

10. Stability and Reactivity

Reactivity

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Chemical stability

The product is chemically stable.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Incompatible materials to avoid

not required under normal use

Hazardous decomposition products

None known

11. Toxicological Information

Information on toxicological effects

General observations

There is no data available on the product. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1272/2008/EC and classified for toxicological hazards accordingly. See sections 2 and 3 for details.

Practical experience

Swallowing may cause nausea, diarrhoea, vomiting and gastro-intestinal irritation.

Acute toxicity

Acute inhalation toxicity

Based on available data, the classification criteria are not met.

Acute dermal toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

Based on available data, the classification criteria are not met.

Irritation

Eyes

Based on available data, the classification criteria are not met.

Skin

Based on available data, the classification criteria are not met.

Corrosion

Eyes

Based on available data, the classification criteria are not met.

Skin

Based on available data, the classification criteria are not met.

Sensitisation

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

12. Ecological Information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. The data in this section is consistent with data from chemical safety reports available at the date of revision.

Toxicity

No information available.

Persistence and degradability

No information available.

Bio accumulative potential

No information available.

Mobility in soil

No information available.

Results of PBT and vPvB assessment

Based on available data no ingredient is classified for this hazard property (please see section 3).

Other adverse effects

The preparation was evaluated in accordance with the conventional method of the preparation directive 1272/2008/EG and was not classified as environmental dangerous.

Adsorbed organic bound halogens (AOX)

Product does not contain organic linked halogens contributing to AOX.

13. Disposal considerations

Waste treatment methods

Dispose of in accordance with local regulations.

Product

Recommendation:

A disposal process that converts the waste into energy is recommended. Can be landfilled or incinerated, when in compliance with local regulations.

Waste Key	
Number	Description
080201	Waste coating powders

Uncleaned packaging

Recommendation:

Empty containers can be landfilled, when in accordance with the local regulations. Properly emptied composite packaging is to dispose of as commercial waste (waste keynumber 150105).

14. Transport Information

Not classified as dangerous in the meaning of transport regulations.

ADR/RID:in accordance with nota 1 of chapter 2.2.3.1.1

IMDG:in accordance with chapter 2.3.1.3

ICAO/IATA:in accordance with chapter 3.3.1.3

UN number

Not applicable.

UN proper shipping name

Not applicable.

Transport hazard class(es)

Not applicable.

Packaging group

Not applicable.

Environmental hazards

ADR/RID; IMDG; ICAO/IATA: none

Marine pollutant

IMDG: no

Transport in bulk according to Annex II of Marpol and the IBC Code

Deliveries shall only be made based on appropriate packaging and in compliance with traffic laws.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

The product is non-dangerous in accordance with Directive 1999/45/EC.

National legislation

This safety datasheet has been prepared according to British legislation.

The product is labelled according to the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 as amended (CHIP Regulations). The risk associated with the use of this product must be assessed in accordance with the Control of Substances Hazardous to Health (COSHH) Regulations and the Dangerous Substances and Explosive Atmospheres Regulations.

Restricted to professional users.

Chemical safety assessment

No safety checks were carried out on the mixture.

16. Other Information

Full text of H phrases with no. appearing in section 3

Information taken from reference works and the literature. Substance No.

Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC

Other directives, limitations and prohibitor regulations

CAS no: http://support.cas.org/content/chemical-substances http://echa.europa.eu/

http://echa.europa.eu/search-for-chemicals

http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB https://www.cdc.gov/niosh/ipcs/

Regulation (EC) No. 1907/2006 Directive 98/24/EC Directive 2004/37/EC

REGULATION (EC) No 1272/2008

EUR-LEX: http://eur-lex.europa.eu/homepage.html

Exposure limit for the pure substance http://osha.europa.eu/OSHA

Training advice

Regulation (EC) No. 1907/2006 Directive 98/24/EC

Further information

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions, however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.

Annex - Exposure scenarios

Consolidated exposure assessment for industrial use of coating material

The consolidated exposure assessment provides specific information on how a hazardous substance (in a mixture) is to be managed and controlled. It considers specific conditions of use, in order to ensure that a use is safe to humans and the environment. Compliance with operational conditions and risk management measures is required if the exposure assessment is annexed to a mandatory safety data sheet. In this case, identified risk management measures are to be implemented unless the downstream user can ensure safe use in a diverging way.

Consolidated exposure assessment (type 1) for application of powder coatings by spraying

Free short title:

Industrial application of powder coating by electrostatic spraying and/or spraying onto hot substrate

Systematic title based on use descriptors:

Sector of use SU 3

Product category PC9a, PC9b

PROC4 (covering PROC2), PROC8a

Process category (covering

PROC8b), PROC7

Environmental release

category ERC5

Activities covered:

Transferring/loading, spray application, curing of coating material

Contributing scenarios:

PROC4 (covering PROC2)

Transfer of substance or preparation

PROC8a (covering PROC8b)

(charging/discharging)

Industrial spraying; Also applicable for:

PROC7 Hot flocking, in-mould coating

Operational conditions and risk management measures Contributing environmental scenario

Transferring/loading, spray application, curing of coating material


Process conditions:

No transfer to process waste water stream; specific assessment of environmental exposure obsolete

Contributing worker scenarios

Transferring/loading, spray application, curing of coating material

	PROC	DOA	LEV/T	RVRPE	DPE
Transferring	8a (covering 8b)	> 4	hTRV	no	ves level 2



Further specification:

Above parameters represent standard (default) assumptions according to CEPE mapping of operational conditions Valid information on risk management measures for specific formulation is provided in part 3. Deviation options are explained in part 4 (scaling).

Exposure estimation and reference to its source

Exposure assessment bases on initial scenarios for the used chemicals in this preparation as provided by manufacturers and importers. Identification of a lead substance indicator per route is based on the DPD+ methodology, considering content, dustiness and hazard characteristics. Use of the mixture is considered safe when conditions for safe use of the lead substance indicator are respected. Risk assessment is not applicable if no initial exposure scenarios are available.

Environmental assessment

No relevant ecotoxicological impact expected; specific description and assessment of environmental exposure obsolete;

Worker assessment

No relevant toxicological impact expected; specific description and assessment of worker exposure obsolete;

Further specification:

Respiratory protection equipment for PROC 7 only applicable for manual application inside a spray-booth Assessment of PROC 4 resp. 2 only relevant in case of substance release in curing process

Guidance to downstream user to evaluate whether he works inside the boundaries set by the exposure scenario

Part 4 is common and is available at the end of the Annex.

Consolidated exposure assessment (type 3) for sanding

Free short title:

Industrial sanding of cured coating

Systematic title based on use descriptors:

Sector of use SU 3

PC9a,

Product category PC9b

Process category PROC24

Environmental release

category ERC12a

Activities covered:

Sanding of cured coating

Contributing scenarios:

spERC x4 Wet sanding/wet dust collection in serial production

Applicable for: Sanding, grinding, chipping or

PROC24 polishing of cured coating film

Operational conditions and risk management measures

Contributing environmental scenario

Sanding of cured coating

Process conditions:

Potential transfer to process waste water stream when applying wet sanding techniques or wet dust collection

		Transfer to Release	process Municipal
		waste water	after on-siteSTP
spERC x4 (solids)	Solids in dry film	2%	10%

Contributing worker scenarios

Sanding of cured coating

PROCDOA LEV/TRVRPEDPE

no yes
Sanding24> 4 hLEV | level 2

Further specification:

Above parameters represent standard (default) assumptions according to CEPE mapping of operational conditions Valid information on risk management measures for specific formulation is provided in part 3. Deviation options are explained in part 4 (scaling).

Exposure estimation and reference to its source

Exposure assessment bases on initial scenarios for the used chemicals in this preparation as provided by manufacturers and importers. Identification of a lead substance indicator per route is based on the DPD+ methodology, considering content, dustiness and hazard characteristics. Use of the mixture is considered safe when conditions for safe use of the lead substance indicator are respected. Risk assessment is not applicable if no initial exposure scenarios are available.

Environmental assessment

No relevant ecotoxicological impact expected; specific description and assessment of environmental exposure obsolete;

Worker assessment

No relevant toxicological impact expected; specific description and assessment of worker exposure obsolete;

Guidance to downstream user to evaluate whether he works inside the boundaries set by the exposure scenario

By variation of operational conditions and risk management measures (scaling), a downstream user can check whether he works inside the exposure scenario boundaries.

Standard scaling can be based on exposure modifying factors as used by ECETOC TRA which are listed below.

RCR(s) = RCR(o) * EMF(s)/EMF(o)

RCR(s) shall be < 1

RCR(s) = scaled risk characterisation ratio; RCR(o) = original risk characterisation ratio (in part 3)

EMF(s) = exposure modifying factor selected for scaling; EMF(o) = original exposure modifying factor (in part 3)

Scaling may be used consecutively for multiple determinants.

Example: No technical room ventilation for transferring of powder coatings (EMF(o) = 0.3), duration of activity restricted to 1 h/d (EMF(s) = 0.2)

Specific scaling may be based on measured values at the individual site.

Conte nt	ContentD OA	D O A Fa	Respirat prote ory c-	
%	Factor	ct	tion	
range	h	or	equipment	Fact
> 25	1>4	1		Fact or
	0.61 - 4	0,6	No RPE	1
	0.20,2 5-1	0,2	Filter mask	0,1L evel 1
	0.1<0, 25	0,1	Air-fed mask	0,05 Lev el 2

Skin protection equipment Factor No gloves 1 0,2Le Suitable gloves vel 1 Resistant gloves, 0,1Le vel 2 training 0,05L Resistant gloves, specific training evel 3

PROC Factor for TRV Factor for LEV Industrial setting Factor for LEV Dermal impact

2	0.3	0.1	0.1
۷	0.3	0.1	0.1

7		0.05	0.05	
8a	0.3	0.1	0.01	
8b	0.3	Sol 0.05	0.1	
		Vol		
8b	0.3	0.03	0.1	
2				
2		0.2	0.1	