

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

<b>1 Identification of substance</b>																								
<p><b>Product details</b></p> <ul style="list-style-type: none"> <li>· Trade name: <b>High build etch primer</b></li> <li>· Application of the substance / the preparation <i>Primer</i></li> <li>· Supplier: WHEELPAINTS NN5 5JF UNITED KINGDOM Tel.: 0044(0) 8703-922-0 Fax.: 0044(0) 8703-922-100 e-mail: sales@wheelpaints.co.uk www.wheelpaints.co.uk</li> </ul>																								
<b>2 Composition/Data on components</b>																								
<ul style="list-style-type: none"> <li>· <b>Chemical characterization</b></li> <li>· <b>Description:</b> Mixture of the substances listed below with nonhazardous additions.</li> </ul>																								
<ul style="list-style-type: none"> <li>· <b>Dangerous components:</b></li> </ul>																								
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">1330-20-7</td> <td style="width: 65%;">xylene</td> <td style="width: 20%; text-align: right;">10-25%</td> </tr> <tr> <td>71-36-3</td> <td>butan-1-ol</td> <td style="text-align: right;">10-25%</td> </tr> <tr> <td>123-86-4</td> <td>n-butyl acetate</td> <td style="text-align: right;">2.5-10%</td> </tr> <tr> <td>7779-90-0</td> <td>Preparation based on zincphosphate (supplier's classification)</td> <td style="text-align: right;">2.5-10%</td> </tr> <tr> <td>25068-38-6</td> <td>bisphenole</td> <td style="text-align: right;">2.5-10%</td> </tr> <tr> <td>112-07-2 2-</td> <td>butoxyethyl acetate</td> <td style="text-align: right;">2.5-10%</td> </tr> <tr> <td>64-17-5</td> <td>ethanol</td> <td style="text-align: right;">≤ 2.5%</td> </tr> <tr> <td>64742-95-6</td> <td>Solvent naphtha (petroleum), light arom.</td> <td style="text-align: right;">≤ 2.5%</td> </tr> </table>	1330-20-7	xylene	10-25%	71-36-3	butan-1-ol	10-25%	123-86-4	n-butyl acetate	2.5-10%	7779-90-0	Preparation based on zincphosphate (supplier's classification)	2.5-10%	25068-38-6	bisphenole	2.5-10%	112-07-2 2-	butoxyethyl acetate	2.5-10%	64-17-5	ethanol	≤ 2.5%	64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%
1330-20-7	xylene	10-25%																						
71-36-3	butan-1-ol	10-25%																						
123-86-4	n-butyl acetate	2.5-10%																						
7779-90-0	Preparation based on zincphosphate (supplier's classification)	2.5-10%																						
25068-38-6	bisphenole	2.5-10%																						
112-07-2 2-	butoxyethyl acetate	2.5-10%																						
64-17-5	ethanol	≤ 2.5%																						
64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%																						
<b>3 Hazards identification</b>																								
<p><b>Hazard description:</b> Harmful</p> <ul style="list-style-type: none"> <li>· <b>Information pertaining to particular dangers for man and environment:</b> The product has to be labelled due to the calculation procedure of international guidelines. Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Risk of serious damage to eyes. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</li> <li>· <b>Classification system:</b> The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data. (Contd. on page 2)</li> </ul>																								
<p><b>NFPA ratings (scale 0 - 4)</b> Health = 2 Fire = 3 Reactivity = 0 Reactivity = 0</p>																								
<b>4 First aid measures</b>																								
<p><b>General information:</b> Symptoms of poisoning may even occur after several hours; therefore medical observation for at least</p>																								

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

48  
 hours after the accident.  
 · **After inhalation:**  
 Supply fresh air and to be sure call for a doctor.  
 In case of unconsciousness place patient stably in side position for transportation.  
 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.  
 · **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.  
 · **After swallowing:** If symptoms persist consult doctor.

### 5 Fire fighting measures

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.  
 · **For safety reasons unsuitable extinguishing agents:** Water with full jet  
 · **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.  
 · **Measures for environmental protection:**  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.  
 · **Measures for cleaning/collecting:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.  
 Do not flush with water or aqueous cleansing agents

### \* 7 Handling and storage

· **Handling:**  
 · **Information for safe handling:**  
 Ensure good ventilation/exhaustion at the workplace.  
 Prevent formation of aerosols.  
 · **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 · **Storage:**  
 · **Requirements to be met by storerooms and receptacles:** No special requirements.  
 · **Information about storage in one common storage facility:** Store away from foodstuffs.  
 · **Further information about storage conditions:** Keep receptacle tightly sealed.

### 8 Exposure controls and personal protection

**1330-20-7 xylene**

PEL ()	435 mg/m <sup>3</sup> , 100 ppm
REL ()	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV ()	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**71-36-3 butan-1-ol**

PEL ()	300 mg/m <sup>3</sup> , 100 ppm
REL ()	Short-term value: C 150 mg/m <sup>3</sup> , C 50 ppm Skin
TLV ()	61 mg/m <sup>3</sup> , 20 ppm

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

<b>123-86-4 n-butyl acetate</b>	
PEL () REL () TLV ()	710 mg/m <sup>3</sup> , 150 ppm Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm Short-term value: 950 mg/m <sup>3</sup> , 200 ppm <b>Long-term value: 713 mg/m<sup>3</sup>, 150 ppm</b>
<b>112-07-2 2-butoxyethyl acetate</b>	
REL () TLV ()	33 mg/m <sup>3</sup> , 5 ppm Skin 130 mg/m <sup>3</sup> , 20 ppm
<b>64-17-5 ethanol</b>	
PEL () REL () TLV ()	1900 mg/m <sup>3</sup> , 1000 ppm 1900 mg/m <sup>3</sup> , 1000 ppm 1880 mg/m <sup>3</sup> , 1000 ppm
<p><b>Additional information:</b> The lists that were valid during the creation were used as basis.</p> <ul style="list-style-type: none"> <li>· <b>Personal protective equipment:</b></li> <li>· <b>General protective and hygienic measures:</b>                      Keep away from foodstuffs, beverages and feed.                      Immediately remove all soiled and contaminated clothing.                      Wash hands before breaks and at the end of work.                      Do not inhale gases / fumes / aerosols.                      Avoid contact with the skin.                      Avoid contact with the eyes and skin.</li> <li>· <b>Breathing equipment:</b>                      In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.</li> <li>· <b>Protection of hands:</b>                      Protective gloves                      The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.                      Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation</li> <li>· <b>Material of gloves</b>                      The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>· <b>Penetration time of glove material</b>                      The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.</li> <li>· <b>Eye protection:</b>                      Tightly sealed goggles</li> </ul>	
<b>9 Physical and chemical properties</b>	
<ul style="list-style-type: none"> <li>· <b>General Information</b>  <b>Form:</b> Fluid  <b>Color:</b> According to product specification  <b>Odor:</b> Characteristic</li> <li>· <b>Change in condition</b></li> </ul>	

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 116°C (241°F)

· **Flash point:** 23°C (73°F) (DIN 53213)

· **Ignition temperature:** 340.0°C (644°F) (DIN 51794)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**Explosion limits:**

**Lower:** 1.1 Vol %

**Upper:** 11.3 Vol %

· **Vapor pressure at 20°C (68°F):** 10.7 hPa (8 mm Hg)

· **Density at 20°C (68°F):** 1.202 g/cm<sup>3</sup> (DIN 53217)

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

· **Viscosity:**

**Kinematic at 20°C (68°F):** 125 s (DIN 53211/4)

· **Solvent separation test** < 3 %

· **Solvent content:**

**Organic solvents:** 51.4 %

**Water:** 0.2 %

**VOC content:** 51.4 %

618.6 g/l / 5.16 lb/gl

· **Solids content (weight-%):** 48.4 %

### 10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous products of decomposition:** No dangerous decomposition products known.

### 11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral LD50 4300 mg/kg (rat)

**71-36-3 butan-1-ol**

Oral LD50 790 mg/kg (rat)

Dermal LD50 3400 mg/kg (rabbit)

Inhalative LC50/4 h 8000 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Strong irritant with the danger of severe eye injury.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

### 12 Ecological information

· **Ecotoxic effects:**

· **Acquatic toxicity:**

**7779-90-0 Preparation based on zincphosphate (supplier's classification)**

EC50 63.1 mg/kg (daphnia)

· **Remark:** Harmful to fish

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

· **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Danger to drinking water if even small quantities leak into the ground.*  
*Harmful to aquatic organisms*

### **13 Disposal considerations**

· **Product:**  
 · **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*  
 · **Uncleaned packagings:**  
 · **Recommendation:** *Disposal must be made according to official regulations.*

### **14 Transport information**

· **DOT regulations:**  
 · **Hazard class:** 3  
 · **Identification number:** UN1263  
 · **Packing group:** III  
 · **Proper shipping name (technical name):** PAINT  
 · **Label** 3  
 · **Land transport ADR/RID (cross-border):**  
 · **ADR/RID class:** 3 (F1) Flammable liquids  
 · **Danger code (Kemler):** 30  
 · **UN-Number:** 1263  
 · **Packaging group:** III  
 · **Label:** 3  
 · **Description of goods:** 1263 PAINT, special provision 640E  
 · **Remarks:** ≤ 450 l: -  
 · **Maritime transport IMDG:**  
 · **IMDG Class:** 3  
 · **UN Number:** 1263  
 · **Label** 3  
 · **Packaging group:** III  
 · **EMS Number:** F-E,S-E  
 · **Marine pollutant:** No  
 · **Propper shipping name:** PAINT  
 · **Remarks:** ≤ 30 l: -  
 · **Air transport ICAO-TI and IATA-DGR:**  
 · **ICAO/IATA Class:** 3  
 · **UN/ID Number:** 1263  
 · **Label** 3  
 · **Packaging group:** III  
 · **Propper shipping name:** PAINT

### **15 Regulations**

· **Sara**  
 · **Section 355 (extremely hazardous substances):**  
*None of the ingredient is listed.*  
 · **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene	
71-36-3	butan-1-ol	
7664-38-2	phosphoric acid	
1344-28-1	aluminium oxide	
78-93-3	butanone	

· **TSCA (Toxic Substances Control Act):**

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 ethanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene D

71-36-3 butan-1-ol D

78-93-3 butanone D

· **IARC (International Agency for Research on Cancer)**

1330-20-7 xylene 3

13463-67-7 titanium dioxide 2B

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) 3

· **NTP (National Toxicology Program)**

14808-60-7 Quartz (SiO<sub>2</sub>) K

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene A4 10-25%

13463-67-7 titanium dioxide A4 10-25%

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) A4 2,5-10%

64-17-5 ethanol A4 ≤2,5%

1344-28-1 aluminium oxide A4 ≤2,5%

1314-23-4 zirconium dioxide A4 ≤2,5%

14808-60-7 Quartz (SiO<sub>2</sub>) A2 ≤2,5%

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO<sub>2</sub>)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful

· **Hazard-determining components of labelling:**

bisphenole

xylene

· **Risk phrases:**

Flammable.

Harmful by inhalation and in contact with skin.

Irritating to skin.

Risk of serious damage to eyes.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

Keep out of the reach of children.

Do not breathe fumes/aerosol.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable protective clothing, gloves and eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

# WHEELPAINTS

## MATERIAL SAFETY DATA SHEETS

· **National regulations:**

· **Information about limitation of use:**

64-17-5 ethanol	5
1344-28-1 aluminium oxide	2
14808-60-7 Quartz (SiO <sub>2</sub> )	1

**Class Share in %**

NK 50-100

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*